

ORDINANCE No. 2025-40

AN ORDINANCE OF THE MAYOR AND THE CITY COUNCIL OF THE CITY OF DORAL, FLORIDA, AMENDING CHAPTER 23 OF THE CITY'S CODE OF ORDINANCES TO COMPLY WITH FLORIDA LEGISLATION SB180; PROVIDING FOR INCORPORATION INTO THE CODE; PROVIDING FOR SEVERABILITY; PROVIDING FOR CONFLICTS, AND PROVIDING FOR AN EFFECTIVE DATE

WHEREAS, the Legislature of the State of Florida in Chapter 166 – Municipalities, Florida Statutes, confers upon local governments the authority to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry; and

WHEREAS, the 2025 Florida Legislative Session adopted Senate Bill 180 (SB180) for Emergency Management which removed cumulative substantial improvement for NFIP Compliance; and

WHEREAS, based on the recent changes to the State's Emergency Management requirement on municipalities, it is advisable for the City of Doral to amend its ordinances in order to reflect this change in Florida law.

NOW THEREFORE, BE IT ORDAINED BY THE MAYOR AND THE CITY COUNCIL OF THE CITY OF DORAL AS FOLLOWS:

Section 1. Recitals. The foregoing "WHEREAS" clauses are hereby ratified and confirmed as being true and correct and are hereby made a part of this Ordinance upon adoption hereof.

Section 2. Code Amended. The City Council of the City of Doral hereby approves the amendments to Chapter 23 to read as follows:

SECTION 1. AMENDMENTS.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

Chapter 23 - FLOODS

ARTICLE I. - IN GENERAL

Secs. 23-1—23-100. - Reserved.

ARTICLE II. - FLOODPLAIN MANAGEMENT DIVISION 1. – ADMINISTRATION

Sec. 23-101. - General

23-101.1 Title. These regulations shall be known as the Floodplain Management Ordinance of the City of Doral, hereinafter referred to as "this ordinance."

23-101.2. Scope. The provisions of this article shall apply to all development, including but not limited to the subdivision of land; filling, grading, and other site improvements and utility installations; new construction, alterations, ~~remodeling,~~ additions ~~enlargement, improvement, replacement, repair,~~ relocation or demolition of buildings, structures, and facilities that are exempt from the Florida Building Code; ~~placement, installation, or replacement of manufactured homes and manufactured buildings;~~ installation or replacement of tanks; ~~placement of recreational vehicles;~~ ~~installation of swimming pools;~~ and any other development.

23-101.3 Intent. The purposes of this article and the flood load and flood resistant construction requirements of the Florida Building Code are to establish minimum requirements to safeguard the public health, safety, and general welfare and to minimize public and private losses due to flooding through regulation of development in flood hazard areas to:

- (1) Minimize unnecessary disruption of commerce, access and public service during times of flooding;
- (2) Require the use of appropriate construction practices in order to prevent or minimize future flood damage;
- (3) Manage filling, grading, dredging, mining, paving, excavation, drilling operations, storage of equipment or materials, and other development which may increase flood damage or erosion potential;
- (4) Manage the alteration of flood hazard areas, watercourses, and shorelines to minimize the impact of development on the natural and beneficial functions of the floodplain;
- (5) Minimize damage to public and private facilities and utilities;
- (6) Help maintain a stable tax base by providing for the sound use and development of flood hazard areas;
- (7) Minimize the need for future expenditure of public funds for flood control projects and response to and recovery from flood events;
- (8) Meet the requirements of the National Flood Insurance Program for community participation as set forth in the Title 44 Code of Federal Regulations, Section 59.22;

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

- (9) Restrict or prohibit uses which are dangerous to health, safety and property due to water or erosion hazards, which result in damaging increases in erosion or in flood heights and velocities; and
- (10) Prevent or regulate the construction of flood barriers which will unnaturally divert flood waters, or which may increase flood hazards to other lands.

23-101.4 Coordination with the Florida Building Code. This article is intended to be administered and enforced in conjunction with the Florida Building Code. Where cited, ASCE 24 refers to the edition of the standard that is referenced by the Florida Building Code.

23-101.5 Warning. The degree of flood protection required by this article and the Florida Building Code, as amended by this community, is considered the minimum reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur. Flood heights may be increased by man-made or natural causes. This article does not imply that land outside of mapped special flood hazard areas, or that uses permitted within such flood hazard areas, will be free from flooding or flood damage. The flood hazard areas and base flood elevations contained in the flood insurance study and shown on flood insurance rate maps and the requirements of Title 44 Code of Federal Regulations, Sections 59 and 60 may be revised by the Federal Emergency Management Agency, requiring this community to revise these regulations to remain eligible for participation in the National Flood Insurance Program. No guaranty of vested use, existing use, or future use is implied or expressed by compliance with this article.

23-101.6 Disclaimer of liability. This article shall not create liability on the part of the Mayor and City Council of the City of Doral or by any officer or employee thereof for any flood damage that result from reliance on this article or any administrative decision lawfully made thereunder.

Sec. 23-102. - Applicability.

23-102.1 General. Where there is a conflict between a general requirement and a specific requirement, the specific requirement shall be applicable.

23-102.2 Areas to which this article applies. This article shall apply to all areas within the City of Doral.

23-102.3 Basis for establishing flood hazard areas. The Flood Insurance Study for Miami-Dade County and Incorporated Areas dated September 11, 2009, and all subsequent amendments and revisions, and the accompanying flood insurance rate maps (FIRM), and all subsequent amendments and revisions to such maps, are adopted by reference as a part of this article and shall serve as the minimum basis for establishing flood hazard areas. Studies and maps that establish flood hazard areas are on file at the City of Doral Building Department, 8401 NW 53 Terrace, Doral, FL 33166.

23-102.3.1 Submission of additional data to establish flood hazard areas. To establish flood hazard areas and base flood elevations, pursuant to ~~division 1,~~

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

~~subdivision V~~ 23-105 of this article the floodplain administrator may require submission of additional data. Where field surveyed topography prepared by a Florida licensed professional surveyor or digital topography accepted by the community indicates that ground elevations:

- (1) Are below the closest applicable base flood elevation, even in areas not delineated as a special flood hazard area on a FIRM, the area shall be considered as flood hazard area and subject to the requirements of this article and, as applicable, the requirements of the Florida Building Code.
- (2) Are above the closest applicable base flood elevation, the area shall be regulated as special flood hazard area unless the applicant obtains a letter of map change that removes the area from the special flood hazard area.

23-102.4 Other laws. The provisions of this article shall not be deemed to nullify any provisions of local, state or federal law.

23-102.5 Abrogation and greater restrictions. This article supersedes any ordinance in effect for management of development in flood hazard areas. However, it is not intended to repeal or abrogate any existing ordinances including but not limited to land development regulations, zoning ordinances, stormwater management regulations, or the Florida Building Code. In the event of a conflict between this article and any other ordinance, the more restrictive shall govern. This article shall not impair any deed restriction, covenant or easement, but any land that is subject to such interests shall also be governed by this article.

23-102.6 Interpretation. In the interpretation and application of this article, all provisions shall be:

- (1) Considered as minimum requirements;
- (2) Liberally construed in favor of the governing body; and
- (3) Deemed neither to limit nor repeal any other powers granted under state statutes.

Sec. 23-103. - Duties and powers of the floodplain administrator.

23-103.1 Designation. The city council hereby appoints the floodplain ~~manager~~ administrator. ~~a specific position in the building department or his/her designee~~ The floodplain administrator may designate the floodplain manager, a specific position in the building department to administer and implement the provisions of this article. ~~and is herein referred to as the floodplain administrator.~~

23-103.2 General. The floodplain administrator is authorized and directed to administer and enforce the provisions of this article. The floodplain administrator shall have the authority to render interpretations of this article consistent with the intent and purpose of this article and may establish policies and procedures in order to clarify the application of its provisions. Such interpretations, policies, and procedures shall not have the effect of waiving requirements specifically provided in this article without the granting of a variance pursuant to ~~division 1, subdivision VII~~ 23-107 of this article.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

23-103.3 Applications and permits. The floodplain administrator, in coordination with other pertinent offices of the community, shall:

- (1) Review applications and plans to determine whether proposed new development will be located in flood hazard areas;
- (2) Review applications for modification of any existing development in flood hazard areas for compliance with the requirements of this article;
- (3) Interpret flood hazard area boundaries where such interpretation is necessary to determine the exact location of boundaries; a person contesting the determination shall have the opportunity to appeal the interpretation;
- (4) Provide available flood elevation and flood hazard information;
- (5) Determine whether additional flood hazard data shall be obtained from other sources or shall be developed by an applicant;
- (6) Review applications to determine whether proposed development will be reasonably safe from flooding;
- (7) Issue floodplain development permits or approvals for development other than buildings and structures that are subject to the Florida Building Code, including buildings, structures and facilities exempt from the Florida Building Code, when compliance with this article is demonstrated, or disapprove the same in the event of noncompliance; and
- (8) Coordinate with and provide comments to the building official to assure that applications, plan reviews, and inspections for buildings and structures comply with the applicable provisions of this article.

23-103.4 Substantial improvement and substantial damage determinations.

For applications for building permits to improve buildings and structures, including alterations, movement, ~~enlargement, replacement, repair, change of occupancy,~~ additions, ~~rehabilitations, renovations,~~ substantial improvements and repairs of substantial damage, ~~and any other improvement of or work on~~ such buildings and structures, the floodplain administrator, in coordination with the building official, shall:

- (1) Estimate the market value, or require the applicant to obtain an appraisal of the market value prepared by a qualified independent appraiser, of the building or structure before the start of construction of the proposed work; in the case of repair of substantial damage, the market value of the building or structure shall be the market value before the damage occurred and before any repairs are made;
- (2) Compare the cost to perform the improvement, the cost to repair a damaged building to its pre-damaged condition, or the combined costs of improvements and repairs, if applicable, to the market value of the building or structure;
- (3) Determine and document whether the proposed work constitutes substantial improvement or repair of substantial damage; ~~the determination requires evaluation of previous permits issued for improvements and repairs as specified in the definition of "substantial improvement"; for proposed work to~~

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

~~repair damage caused by flooding, the determination requires evaluation of previous permits issued to repair flood-related damage as specified in the definition of "substantial damage"; and~~

- (4) Notify the applicant if it is determined that the work constitutes substantial improvement or repair of substantial damage and that compliance with the flood resistant construction requirements of the Florida Building Code and this article is required.

Pursuant to §163.31795, F.S., the City shall not adopt or enforce any provision that includes a cumulative substantial improvement period. Each determination of substantial improvement shall be based solely on the cost of a single proposed improvement project relative to the market value of the structure at the time of permit application. Nothing herein shall preclude the City from enforcing substantial damage provisions as defined by the NFIP and the Florida Building Code.

23-103.5 Modifications of the strict application of the requirements of the Florida Building Code. The floodplain administrator shall review requests submitted to the building official that seek approval to modify the strict application of the flood load and flood resistant construction requirements of the Florida Building Code to determine whether such requests require the granting of a variance pursuant to ~~division 1, subdivision VII~~ 23-107 of this article.

23-103.6 Notices and orders. The floodplain administrator shall coordinate with appropriate local agencies for the issuance of all necessary notices or orders to ensure compliance with this article.

23-103.7 Inspections. The floodplain administrator shall make the required inspections as specified in 23-106 of this article for development that is not subject to the Florida Building Code, including buildings, structures and facilities exempt from the Florida Building Code. The floodplain administrator shall inspect areas to determine if development is undertaken without issuance of a permit.

23-103.8 Other duties of the floodplain administrator. The floodplain administrator shall have other duties, including but not limited to:

- (1) Establish, in coordination with the building official, procedures for administering and documenting determinations of substantial improvement and substantial damage made pursuant to section 23-103.4 of this article;
- (2) Require that applicants proposing alteration of a watercourse notify adjacent communities and the Florida Division of Emergency Management, state floodplain management office, and submit copies of such notifications to the Federal Emergency Management Agency (FEMA);
- (3) Require applicants who submit hydrologic and hydraulic engineering analyses to support permit applications to submit to FEMA the data and information necessary to maintain the flood insurance rate maps if the analyses propose to change base flood elevations, flood hazard area boundaries, or floodway designations; such submissions shall be made within six months of such data becoming available;

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

- (4) Review required design certifications and documentation of elevations specified by this article and the Florida Building Code and this article to determine that such certifications and documentations are complete; and
- (5) Notify the Federal Emergency Management Agency when the corporate boundaries of the City of Doral are modified.
- (6) Electronically track receipt of elevation certificates, substantial damage certificates, substantial damage estimates, SI/SD letters and floodplain development permits in an electronically formatted database.
- (7) Maintain a post-storm permitting plan including field or remote-permitting when feasible.

Maintain online library of recovery guidance documents and resources, updated annually no later than May 1st.

23-103.9 Floodplain management records. Regardless of any limitation on the period required for retention of public records, the floodplain administrator shall maintain and permanently keep and make available for public inspection all records that are necessary for the administration of this article and the flood resistant construction requirements of the Florida Building Code, including flood insurance rate maps; letters of change; records of issuance of permits and denial of permits; determinations of whether proposed work constitutes substantial improvement or repair of substantial damage; required design certifications and documentation of elevations specified by the Florida Building Code and this article; notifications to adjacent communities, FEMA, and the state related to alterations of watercourses; assurances that the flood carrying capacity of altered watercourses will be maintained; documentation related to appeals and variances, including justification for issuance or denial; and records of enforcement actions taken pursuant to this article and the flood resistant construction requirements of the Florida Building Code. These records shall be available for public inspection at the City of Doral Building Department.

Sec. 23-104. - Permits.

23-104.1 Permits required. Any owner or owner's authorized agent (hereinafter "applicant") who intends to undertake any development activity within the scope of this article, including buildings, structures and facilities exempt from the Florida Building Code, shall first make application to the floodplain administrator, and the building official if applicable, and shall obtain the required permit(s) and approval(s). No such permit or approval shall be issued until compliance with the requirements of this article, and all other applicable codes and regulations has been satisfied.

23-104.2 Floodplain development permits or approvals. Floodplain development permits or approvals shall be issued pursuant to this article for any development activities not subject to the requirements of the Florida Building Code, including buildings, structures and facilities exempt from the Florida Building Code. Depending on the nature and extent of proposed development that includes a building or structure, the floodplain administrator may determine that a floodplain development permit or approval is required in addition to a building permit.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

23-104.2.1 Buildings, structures and facilities exempt from the Florida Building Code. Pursuant to the requirements of federal regulation for participation in the National Flood Insurance Program (44 C.F.R. Sections 59 and 60), floodplain development permits or approvals shall be required for the following buildings, structures and facilities that are exempt from the Florida Building Code and any further exemptions provided by law, which are subject to the requirements of this article:

- (1) Railroads and ancillary facilities associated with the railroad.
- (2) Nonresidential farm buildings on farms, as provided in F.S. § 604.50.
- (3) Temporary buildings or sheds used exclusively for construction purposes.
- (4) Mobile or modular structures used as temporary offices.
- (5) Those structures or facilities of electric utilities, as defined in F.S. § 366.02, which are directly involved in the generation, transmission, or distribution of electricity.
- (6) Chickees constructed by the Miccosukee Tribe of Indians of Florida or the Seminole Tribe of Florida. As used in this paragraph, the term "chickee" means an open-sided wooden hut that has a thatched roof of palm or palmetto or other traditional materials, and that does not incorporate any electrical, plumbing, or other non-wood features.
- (7) Family mausoleums not exceeding 250 square feet in area which are prefabricated and assembled on site or preassembled and delivered on site and have walls, roofs, and a floor constructed of granite, marble, or reinforced concrete.
- (8) Temporary housing provided by the department of corrections to any prisoner in the state correctional system.
- (9) Structures identified in F.S. § 553.73(10)(k), are not exempt from the Florida Building Code if such structures are located in flood hazard areas established on flood insurance rate maps.

23-104.3 Application for a permit or approval. To obtain a floodplain development permit or approval the applicant shall first file an application in writing on a form furnished by the community. The information provided shall:

- (1) Identify and describe the development to be covered by the permit or approval.
- (2) Describe the land on which the proposed development is to be conducted by legal description, street address or similar description that will readily identify and definitively locate the site.
- (3) Indicate the use and occupancy for which the proposed development is intended.
- (4) Be accompanied by a site plan or construction documents as specified in division 1, subdivision V 23-105 of this article.
- (5) State the valuation of the proposed work.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

- (6) For projects proposing to enclose areas under elevated buildings, a signed non-conversion agreement; the agreement shall be recorded on the property deed prior to issuance of the certificate of occupancy.
- (7) Be signed by the applicant or the applicant's authorized agent.
- (8) Give such other data and information as required by the floodplain administrator.

23-104.4 Validity of permit or approval. The issuance of a floodplain development permit or approval pursuant to this article shall not be construed to be a permit for, or approval of, any violation of this article, the Florida Building Codes, or any other ordinance of this community. The issuance of permits based on submitted applications, construction documents, and information shall not prevent the floodplain administrator from requiring the correction of errors and omissions.

23-104.5 Expiration. A floodplain development permit or approval shall become invalid unless the work authorized by such permit is commenced within 180 days after its issuance, or if the work authorized is suspended or abandoned for a period of 180 days after the work commences. Extensions for periods of not more than 180 days each shall be requested in writing and justifiable cause shall be demonstrated.

23-104.6 Suspension or revocation. The floodplain administrator is authorized to suspend or revoke a floodplain development permit or approval if the permit was issued in error, on the basis of incorrect, inaccurate or incomplete information, or in violation of this article or any other ordinance, regulation or requirement of this community.

23-104.7 Other permits required. Floodplain development permits and building permits shall include a condition that all other applicable state or federal permits be obtained before commencement of the permitted development, including but not limited to the following:

- (1) The South Florida Water Management District; F.S. § 373.036.
- (2) Florida Department of Health for onsite sewage treatment and disposal systems; F.S. § 381.0065, and Chapter 64E-6, F.A.C.
- (3) Florida Department of Environmental Protection for activities subject to the Joint Coastal Permit; F.S. § 161.055.
- (4) Florida Department of Environmental Protection for activities that affect wetlands and alter surface water flows, in conjunction with the U.S. Army Corps of Engineers; Section 404 of the Clean Water Act.
- (5) Federal permits and approvals.

Sec. 23-105. - Site plans and construction documents.

23-105.1 Information for development. The site plan or construction documents for any development subject to the requirements of this article shall be drawn to scale and shall include, as applicable to the proposed development:

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

- (1) Delineation of flood hazard areas, floodway boundaries and flood zone(s), base flood elevation(s), and ground elevations if necessary for review of the proposed development if not provided on the Permit Application.
- (2) Where base flood elevations, or floodway data are not included on the FIRM or in the flood insurance study, they shall be established in accordance with section 23-105.2(2) or (3) of this article.
- (3) Where the parcel on which the proposed development will take place will have more than 50 lots or is larger than five acres and the base flood elevations are not included on the FIRM or in the flood insurance study, such elevations shall be established in accordance with section 23-105.2(1) of this article.
- (4) Location of the proposed activity and proposed structures, and locations of existing buildings and structures.
- (5) Location, extent, amount, and proposed final grades of any filling, grading, or excavation.
- (6) Where the placement of fill is proposed, the amount, type, and source of fill material; compaction specifications; a description of the intended purpose of the fill areas; and evidence that the proposed fill areas are the minimum necessary to achieve the intended purpose.
- (7) Existing and proposed alignment of any proposed alteration of a watercourse.

The floodplain administrator is authorized to waive the submission of site plans, construction documents, and other data that are required by this article but that are not required to be prepared by a registered design professional if it is found that the nature of the proposed development is such that the review of such submissions is not necessary to ascertain compliance with this article.

23-105.2 Information in flood hazard areas without base flood elevations (approximate zone A). Where flood hazard areas are delineated on the FIRM and base flood elevation data have not been provided, the floodplain administrator shall:

- (1) Require the applicant to include base flood elevation data prepared in accordance with currently accepted engineering practices.
- (2) Obtain, review, and provide to applicants base flood elevation and floodway data available from a federal or state agency or other source or require the applicant to obtain and use base flood elevation and floodway data available from a federal or state agency or other source.
- (3) Where base flood elevation and floodway data are not available from another source, where the available data are deemed by the floodplain administrator to not reasonably reflect flooding conditions, or where the available data are known to be scientifically or technically incorrect or otherwise inadequate:
 - a. Require the applicant to include base flood elevation data prepared in accordance with currently accepted engineering practices; or
 - b. Specify that the base flood elevation is three feet above the highest adjacent grade at the location of the development, provided there is no

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

evidence indicating flood depths have been or may be greater than three feet.

- (4) Where the base flood elevation data are to be used to support a letter of map change from FEMA, advise the applicant that the analyses shall be prepared by a Florida licensed engineer in a format required by FEMA, and that it shall be the responsibility of the applicant to satisfy the submittal requirements and pay the processing fees.

23-105.3 Additional analyses and certifications. As applicable to the location and nature of the proposed development activity, and in addition to the requirements of this section, the applicant shall have the following analyses signed and sealed by a Florida licensed engineer for submission with the site plan and construction documents:

- (1) For development activities proposed to be located in a regulatory floodway, a floodway encroachment analysis that demonstrates that the encroachment of the proposed development will not cause any increase in base flood elevations; where the applicant proposes to undertake development activities that do increase base flood elevations, the applicant shall submit such analysis to FEMA as specified in section 23-105.4 of this article and shall submit the conditional letter of map revision, if issued by FEMA, with the site plan and construction documents.
- (2) For development activities proposed to be located in a riverine flood hazard area for which base flood elevations are included in the flood insurance study or on the FIRM and floodways have not been designated, hydrologic and hydraulic analyses that demonstrate that the cumulative effect of the proposed development, when combined with all other existing and anticipated flood hazard area encroachments, will not increase the base flood elevation more than one foot at any point within the community. This requirement does not apply in isolated flood hazard areas not connected to a riverine flood hazard area or in flood hazard areas identified as zone AO or zone AH.
- (3) For alteration of a watercourse, an engineering analysis prepared in accordance with standard engineering practices which demonstrates that the flood-carrying capacity of the altered or relocated portion of the watercourse will not be decreased, and certification that the altered watercourse shall be maintained in a manner which preserves the channel's flood-carrying capacity; the applicant shall submit the analysis to FEMA as specified in section 23-105.4 of this article.

23-105.4 Submission of additional data. When additional hydrologic, hydraulic or other engineering data, studies, and additional analyses are submitted to support an application, the applicant has the right to seek a letter of map change from FEMA to change the base flood elevations, change floodway boundaries, or change boundaries of flood hazard areas shown on FIRMs, and to submit such data to FEMA for such purposes. The analyses shall be prepared by a Florida licensed engineer in a format required by FEMA. Submittal requirements and processing fees shall be the responsibility of the applicant.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

Sec. 23-106. - Inspections.

23-106.1 General. Development for which a floodplain development permit or approval is required shall be subject to inspection.

23-106.1.1 Development other than buildings and structures. The Floodplain Administrator shall inspect all development to determine compliance with the requirements of this article and the conditions of issued floodplain development permits or approvals.

23-106.1.2 Buildings, structures and facilities exempt from the Florida Building Code. The floodplain administrator shall inspect buildings, structures and facilities exempt from the Florida Building Code to determine compliance with the requirements of this article and the conditions of issued floodplain development permits or approvals.

23-106.1.2.1 Buildings, structures and facilities exempt from the Florida Building Code lowest floor inspection. ~~Upon placement of the lowest floor, including basement, and prior to further vertical construction, the owner of a building, structure or facility exempt from the Florida Building Code, or the owner's authorized agent, shall submit to the floodplain administrator:~~ Upon placement of the lowest floor, or floodproofing by whatever construction means, or bottom of the lowest horizontal structural member, and prior to further vertical construction, it shall be the duty of the permit holder to submit to the floodplain administrator a Building Under Construction (BUC) elevation certificate of the NGVD or NAVD elevation of the lowest floor or floodproofed elevation, or bottom of the lowest horizontal structural member of the lowest floor as built, in relation to the datum on the FIRM. Said certification shall be prepared by or under the direct supervision of a registered land surveyor or professional engineer and certified by same. When floodproofing is utilized for a particular building said certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. Any work undertaken prior to submission of the (BUC) certification shall be at the permit holder's risk. The floodplain administrator shall review the lowest floor, and floodproofing elevation survey data submitted. The permit holder immediately and prior to further progressive work being permitted to proceed shall correct violations detected by such review. Failure to submit the BUC or failure to make said corrections required hereby shall be cause to issue a stop-work order for the project.

- (1) If a design flood elevation was used to determine the required elevation of the lowest floor, the certification of elevation of the lowest floor prepared and sealed by a Florida licensed professional surveyor; or
- (2) If the elevation used to determine the required elevation of the lowest floor was determined in accordance with section 23-105.2(3)b. of this article, the documentation of height of the lowest floor above highest adjacent grade, prepared by the owner or the owner's authorized agent.

23-106.1.2.2 Buildings, structures and facilities exempt from the Florida Building Code, final inspection. As part of the final inspection, the owner or owner's

authorized agent shall submit to the floodplain administrator a final certification of elevation of the lowest floor or final documentation of the height of the lowest floor above the highest adjacent grade; such certifications and documentations shall be prepared as specified in section 23-106.1.2.1 of this article. Failure to submit the required documentation may result in a violation in accordance with section 23-109.

Sec. 23-107. - Variances and appeals.

23-107.1 General. The city council shall hear and decide on requests for appeals and requests for variances from the strict application of this article. Pursuant to F.S. § 553.73(5), the city council shall hear and decide on requests for appeals and requests for variances from the strict application of the flood resistant construction requirements of the Florida Building Code. Applications for variances to this chapter shall be processed in accordance with section 33-304 of the City Code.

23-107.2 Appeals. The city council shall hear and decide appeals when it is alleged there is an error in any requirement, decision, or determination made by the floodplain administrator in the administration and enforcement of this article. Any person aggrieved by the decision of city council may appeal such decision to the Circuit Court, as provided by Florida Statutes.

23-107.3 Limitations on authority to grant variances. The city council shall base its decisions on variances on technical justifications submitted by applicants, the considerations for issuance in section 23-107.6 of this article, the conditions of issuance set forth in section 23-107.7 of this article, and the comments and recommendations of the floodplain administrator and the building official. The city council has the right to attach such conditions as it deems necessary to further the purposes and objectives of this article.

23-107.3.1 Restrictions in floodways. A variance shall not be issued for any proposed development in a floodway if any increase in base flood elevations would result, as evidenced by the applicable analyses and certifications required in section 23-105.3 of this article.

23-107.4 Historic buildings. A variance is authorized to be issued for the repair, improvement, or rehabilitation of a historic building that is determined eligible for the exception to the flood resistant construction requirements of the Florida Building Code, Existing Building, Chapter 44 12 Historic Buildings, upon a determination that the proposed repair, improvement, or rehabilitation will not preclude the building's continued designation as a historic building and the variance is the minimum necessary to preserve the historic character and design of the building. If the proposed work precludes the building's continued designation as a historic building, a variance shall not be granted and the building and any repair, improvement, and rehabilitation shall be subject to the requirements of the Florida Building Code.

23-107.5 Functionally dependent uses. A variance is authorized to be issued for the construction or substantial improvement necessary for the conduct of a functionally dependent use, as defined in this article, provided the variance meets the requirements of section 23-107.3.1, is the minimum necessary considering the flood

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

hazard, and all due consideration has been given to use of methods and materials that minimize flood damage during occurrence of the base flood.

23-107.6 Considerations for issuance of variances. In reviewing requests for variances, the city council shall consider all technical evaluations, all relevant factors, all other applicable provisions of the Florida Building Code, this article, and the following:

- (1) The danger that materials and debris may be swept onto other lands resulting in further injury or damage;
- (2) The danger to life and property due to flooding or erosion damage;
- (3) The susceptibility of the proposed development, including contents, to flood damage and the effect of such damage on current and future owners;
- (4) The importance of the services provided by the proposed development to the community;
- (5) The availability of alternate locations for the proposed development that are subject to lower risk of flooding or erosion;
- (6) The compatibility of the proposed development with existing and anticipated development;
- (7) The relationship of the proposed development to the comprehensive plan and floodplain management program for the area;
- (8) The safety of access to the property in times of flooding for ordinary and emergency vehicles;
- (9) The expected heights, velocity, duration, rate of rise and debris and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site; and
- (10) The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, streets and bridges.

23-107.7 Conditions for issuance of variances. Variances shall be issued only upon:

- (1) Submission by the applicant, of a showing of good and sufficient cause that the unique characteristics of the size, configuration, or topography of the site limit compliance with any provision of this article or the required elevation standards;
- (2) Determination by the city council that:
 - a. Failure to grant the variance would result in exceptional hardship due to the physical characteristics of the land that render the lot undevelopable; increased costs to satisfy the requirements or inconvenience do not constitute hardship;
 - b. The granting of a variance will not result in increased flood heights,

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

additional threats to public safety, extraordinary public expense, nor create nuisances, cause fraud on or victimization of the public or conflict with existing local laws and ordinances; and

- c. The variance is the minimum necessary, considering the flood hazard, to afford relief;
- (3) Receipt of a signed statement by the applicant that the variance, if granted, shall be recorded in the office of the clerk of the court in such a manner that it appears in the chain of title of the affected parcel of land; and
- (4) If the request is for a variance to allow construction of the lowest floor of a new building, or substantial improvement of a building, below the required elevation, a copy in the record of a written notice from the floodplain administrator to the applicant for the variance, specifying the difference between the base flood elevation and the proposed elevation of the lowest floor, stating that the cost of federal flood insurance will be commensurate with the increased risk resulting from the reduced floor elevation (up to amounts as high as \$25.00 for \$100.00 of insurance coverage), and stating that construction below the base flood elevation increases risks to life and property.

Sec. 23-108. - Real estate disclosure.

23-108 Real estate disclosure. In any contract for the sale of improved real estate located within the City of Doral which is in a special flood hazard area, the seller shall include in the contract or a rider to the contract the following disclosure in not less than ten-point bold faced type:

THIS HOME OR STRUCTURE IS LOCATED IN A SPECIAL FLOOD HAZARD AREA. IF THIS HOME OR STRUCTURE IS BELOW THE APPLICABLE FLOOD ELEVATION LEVEL AND IS SUBSTANTIALLY DAMAGED OR SUBSTANTIALLY IMPROVED, AS DEFINED IN THE CITY OF DORAL FLOODPLAIN MANAGEMENT ORDINANCE, IT MAY, AMONG OTHER THINGS, BE REQUIRED TO BE RAISED TO THE APPLICABLE FLOOD ELEVATION LEVEL.

Sec. 23-109. - Violations.

23-109.1 Violations. Any development that is not within the scope of the Florida Building Code but that is regulated by this article that is performed without an issued permit, that is in conflict with an issued permit, or that does not fully comply with this article, shall be deemed a violation of this article. A building or structure without the documentation of elevation of the lowest floor, other required design certifications, or other evidence of compliance required by this article or the Florida Building Code is presumed to be a violation until such time as that documentation is provided.

23-109.2 Authority. For development that is not within the scope of the Florida Building Code but that is regulated by this article and that is determined to be a violation, the floodplain administrator is authorized to serve notices of violation or stop work orders to owners of the property involved, to the owner's agent, or to the person CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

or persons performing the work.

23-109.3 Unlawful continuance. Any person who shall continue any work after having been served with a notice of violation or a stop work order, except such work as that person is directed to perform to remove or remedy a violation or unsafe condition, shall be subject to penalties as prescribed by law.

23-109.4 Violation. Violation of the provisions of this article or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall be punishable for a non- criminal violation. Any person who violates this article or fails to comply with any of its requirements shall, upon adjudication therefore, be fined not more than \$500.00, and in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent the floodplain administrator from taking such other lawful actions as is necessary to prevent or remedy any violation.

DIVISION 2. - DEFINITIONS

Sec. 23-201. - General.

23-201.1 Scope. Unless otherwise expressly stated, the following words, terms and phrases, when used in this section, shall have the meanings ascribed to them in this section, except where the context clearly indicates a different meaning.

23-201.2 Terms defined in the Florida Building Code. Where terms are not defined in this article and are defined in the Florida Building Code, such terms shall have the meanings ascribed to them in that code.

23-201.3 Terms not defined. Where terms are not defined in this article or in the Florida Building Code, such terms shall have ordinarily accepted meanings such as the context implies.

Sec. 23-202. - Definitions.

Accessory structure. A structure on the same parcel of property as a principal structure and the use of which is incidental to the use of the principal structure. For floodplain management purposes, the term includes only accessory structures used for parking and storage.

Alteration of a watercourse. A dam, impoundment, channel relocation, change in channel alignment, channelization, or change in cross-sectional area of the channel or the channel capacity, or any other form of modification which may alter, impede, retard or change the direction and/or velocity of the riverine flow of water during conditions of the base flood.

Appeal. A request for a review of the floodplain administrator's interpretation of any provision of this article or a request for a variance.

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

ASCE 24. A standard titled flood resistant design and construction that is referenced by the Florida Building Code. ASCE 24 is developed and published by the American Society of Civil Engineers, Reston, VA.

Back of sidewalk. The elevation of the highest surface of the sidewalk abutting the property relative to the National Geodetic Vertical Datum (NGVD) or North America Vertical Datum (NAVD). Depending on site conditions, if there is a variation in sidewalk elevations abutting the property, the highest and lowest elevations may be averaged to obtain the regulatory sidewalk elevation provided the elevation is above the base flood elevation.

Base flood. A flood having a 1-percent chance of being equaled or exceeded in any given year. [Also defined in FBC, B, Section 1612.2.] The base flood is commonly referred to as the "100-year flood" or the "1-percent-annual chance flood."

Base flood elevation. The elevation of the base flood, including wave height, relative to the National Geodetic Vertical Datum (NGVD), North American Vertical Datum (NAVD) or other datum specified on the Flood Insurance Rate Map (FIRM). [Also defined in FBC, B, Section 1612.2.]

Basement. The portion of a building having its floor subgrade (below ground level) on all sides. [Also defined in FBC, B, Section 1612.2.]

Crown of road. The elevation of the highest surface of street pavement within the right-of-way abutting the property relative to the National Geodetic Vertical Datum (NGVD) or North America Vertical Datum (NAVD). Depending on site conditions, if there is a variation in the crown elevations abutting the property, the highest and lowest elevations may be averaged to obtain the regulatory crown elevation provided the elevation is above the base flood elevation.

Design flood. The flood associated with the greater of the following two areas: [Also defined in FBC, B, Section 1612.2.]

- (1) Area with a floodplain subject to a 1-percent or greater chance of flooding in any year; or
- (2) Area designated as a flood hazard area on the community's flood hazard map, or otherwise legally designated.

Design flood elevation. The elevation of the "design flood," including wave height, relative to the datum specified on the community's legally designated flood hazard map. In areas designated as zone AO, the design flood elevation shall be the elevation of the highest existing grade of the building's perimeter plus the depth number (in feet) specified on the flood hazard map. In areas designated as zone AO where the depth number is not specified on the map, the depth number shall be taken as being equal to two feet. [Also defined in FBC, B, Section 1612.2.]

Development. Any man-made change to improved or unimproved real estate, including but not limited to, buildings or other structures, tanks, temporary structures, temporary or permanent storage of equipment or materials, mining, dredging, filling, grading, paving, excavations, drilling operations or any other land disturbing activities.

Encroachment. The placement of fill, excavation, buildings, permanent structures

or other development into a flood hazard area which may impede or alter the flow capacity of riverine flood hazard areas.

Existing building and existing structure. Any buildings and structures for which the "start of construction" commenced before September 29, 1972.

Federal Emergency Management Agency (FEMA). The federal agency that, in addition to carrying out other functions, administers the National Flood Insurance Program.

Flood or flooding. A general and temporary condition of partial or complete inundation of normally dry land from: [Also defined in FBC, B, Section 1612.2.]

- (1) The overflow of inland or tidal waters.
- (2) The unusual and rapid accumulation or runoff of surface waters from any source.

Flood damage-resistant materials. Any construction material capable of withstanding direct and prolonged contact with floodwaters without sustaining any damage that requires more than cosmetic repair. [Also defined in FBC, B, Section 1612.2.]

Flood hazard area. The greater of the following two areas: [Also defined in FBC, B, Section 1612.2.]

- (1) The area within a floodplain subject to a 1-percent or greater chance of flooding in any year.
- (2) The area designated as a flood hazard area on the community's flood hazard map, or otherwise legally designated.

Flood insurance rate map (FIRM). The official map of the community on which the Federal Emergency Management Agency has delineated both special flood hazard areas and the risk premium zones applicable to the community. [Also defined in FBC, B, Section 1612.2.]

Flood insurance study (FIS). The official report provided by the Federal Emergency Management Agency that contains the flood insurance rate map, the flood boundary and floodway map (if applicable), the water surface elevations of the base flood, and supporting technical data. [Also defined in FBC, B, Section 1612.2.]

Floodplain administrator. The office or position designated and charged with the administration and enforcement of this article ~~(may be referred to as the floodplain manager).~~

Floodplain development permit or approval. An official document or certificate issued by the community, or other evidence of approval or concurrence, which authorizes performance of specific development activities that are determined to be compliant with this article.

Floodplain Manager. A specific position in the Building Department designated by the Floodplain Administrator to administer and implement the provisions of this article.

Floodway. The channel of a river or other riverine watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

cumulatively increasing the water surface elevation more than one foot. [Also defined in FBC, B, Section 1612.2.]

Floodway encroachment analysis. An engineering analysis of the impact that a proposed encroachment into a floodway is expected to have on the floodway boundaries and base flood elevations; the evaluation shall be prepared by a qualified Florida licensed engineer using standard engineering methods and models.

Florida Building Code. The family of codes adopted by the Florida Building Commission, including: Florida Building Code, Building; Florida Building Code, Residential; Florida Building Code, Existing Building; Florida Building Code, Mechanical; Florida Building Code, Plumbing; Florida Building Code, Fuel Gas.

Functionally dependent use. A use which cannot perform its intended purpose unless it is located or carried out in close proximity to water, including only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities; the term does not include long-term storage or related manufacturing facilities.

Highest adjacent grade. The highest natural elevation of the ground surface prior to construction next to the proposed walls or foundation of a structure.

Historic structure. Any structure that is determined eligible for the exception to the flood hazard area requirements of the Florida Building Code, Existing Building, Chapter 44 12 Historic Buildings.

Letter of map change (LOMC). An official determination issued by FEMA that amends or revises an effective flood insurance rate map or flood insurance study. Letters of map change include:

- (1) *Letter of map amendment (LOMA):* An amendment based on technical data showing that a property was incorrectly included in a designated special flood hazard area. A LOMA amends the current effective Flood Insurance Rate Map and establishes that a specific property, portion of a property, or structure is not located in a special flood hazard area.
- (2) *Letter of map revision (LOMR):* A revision based on technical data that may show changes to flood zones, flood elevations, special flood hazard area boundaries and floodway delineations, and other planimetric features.
- (3) *Letter of map revision based on fill (LOMR-F):* A determination that a structure or parcel of land has been elevated by fill above the base flood elevation and is, therefore, no longer located within the special flood hazard area. In order to qualify for this determination, the fill must have been permitted and placed in accordance with the community's floodplain management regulations.
- (4) *Conditional letter of map revision (CLOMR):* A formal review and comment as to whether a proposed flood protection project or other project complies with the minimum NFIP requirements for such projects with respect to delineation of special flood hazard areas. A CLOMR does not revise the effective flood insurance rate map or flood insurance study; upon submission and approval of certified as-built documentation, a letter of map revision may be issued by

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

FEMA to revise the effective FIRM.

Light-duty truck. As defined in 40 C.F.R. 86.082-2, any motor vehicle rated at 8,500 pounds Gross Vehicular Weight Rating or less which has a vehicular curb weight of 6,000 pounds or less and which has a basic vehicle frontal area of 45 square feet or less, which is:

- (1) Designed primarily for purposes of transportation of property or is a derivation of such a vehicle, or
- (2) Designed primarily for transportation of persons and has a capacity of more than 12 persons; or
- (3) Available with special features enabling off-street or off-highway operation and use.

Lowest floor. The lowest floor of the lowest enclosed area of a building or structure, including basement, but excluding any unfinished or flood-resistant enclosure, other than a basement, usable solely for vehicle parking, building access or limited storage provided that such enclosure is not built so as to render the structure in violation of the non-elevation requirements of the Florida Building Code or ASCE 24. [Also defined in FBC, B, Section 1612.2.]

Market value. The price at which a property will change hands between a willing buyer and a willing seller, neither party being under compulsion to buy or sell and both having reasonable knowledge of relevant facts. As used in this article, the term refers to the market value of buildings and structures, excluding the land and other improvements on the parcel. Market value may be established by a qualified independent appraiser, actual cash value (replacement cost depreciated for age and quality of construction), or tax assessment value adjusted to approximate market value by a factor provided by the property appraiser.

New construction. For the purposes of administration of this article and the flood resistant construction requirements of the Florida Building Code, structures for which the "start of construction" commenced on or after September 29, 1972 and includes any subsequent improvements to such structures.

Nonconversion agreement. A form provided by the floodplain administrator to be signed by the owner and recorded on the property deed in official records of the clerk of courts, for the owner to agree not to convert or modify in any manner that is inconsistent with the terms of the building permit and these regulations, enclosures below elevated buildings.

Park trailer. A transportable unit which has a body width not exceeding 14 feet and which is built on a single chassis and is designed to provide seasonal or temporary living quarters when connected to utilities necessary for operation of installed fixtures and appliances. [Defined in F.S. § 320.01, F.S.]

Project. The complete scope of development or work proposed by an applicant that affects a building, structure, or site, as submitted for review and approval by the building department or other permitting authority. A project is defined by the totality of actions identified in a single application or coordinated set of applications intended to

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

achieve a specific improvement objective, and it includes all work reasonably necessary to complete that objective. For purposes of substantial improvement determinations, a project is evaluated as a whole, regardless of whether multiple permits are required to complete it. A project is not limited to the scope of a single permit if multiple permits together accomplish a unified scope of work.

Recreational vehicle. A vehicle, including a park trailer, which is: [see in F.S. § 320.01)

- (1) Built on a single chassis;
- (2) Four hundred square feet or less when measured at the largest horizontal projection;
- (3) Designed to be self-propelled or permanently towable by a light-duty truck; and
- (4) Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

Regulatory crown elevation. Determined by the floodplain manager. See "crown of road" definition.

Regulatory sidewalk elevation. Determined by the floodplain manager. See "back of sidewalk" definition.

Special flood hazard area. An area in the floodplain subject to a one percent or greater chance of flooding in any given year. Special flood hazard areas are shown on FIRMs as zone A, AO, A1-A30, AE, A99, AH, V1-V30, VE or V. [Also defined in FBC, B Section 1612.2.]

Start of construction. The date of issuance for new construction and substantial improvements to existing structures, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement is within 180 days of the date of the issuance. The actual start of construction means either the first placement of permanent construction of a building (including a manufactured home) on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns.

Permanent construction does not include land preparation (such as clearing, grading, or filling), the installation of streets or walkways, excavation for a basement, footings, piers, or foundations, the erection of temporary forms or the installation of accessory buildings such as garages or sheds not occupied as dwelling units or not part of the main buildings. For a substantial improvement, the actual "start of construction" means the first alteration of any wall, ceiling, floor or other structural part of a building, whether or not that alteration affects the external dimensions of the building. [Also defined in FBC, B Section 1612.2.]

Substantial damage. ~~Damage of any origin sustained by a building or structure whereby the cost of restoring the building or structure to its before-damaged condition would equal or exceed 50 percent of the market value of the building or structure before the damage occurred.~~ As defined in Florida Building Code, Building FBC Section 202. The term also includes flood-related damage sustained by a structure on

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strikethrough~~.

two separate occasions during a ten-year period for which the cost of repairs at the time of each such flood event, on average, equals or exceeds 25 percent of structure before the damage occurred.

Substantial improvement. As defined in Florida Building Code, Building FBC Section 202. Any combination of repair, reconstruction, rehabilitation, addition, or other improvement of a building or structure taking place, ~~during a five-year period,~~ the cumulative cost of which equals or exceeds 50 percent of the market value of the building or structure before the improvement or repair is started. ~~For each building or structure, the five-year period begins on the date of the first improvement or repair of that building or structure subsequent to March 12, 2008.~~ If the structure has incurred "substantial damage," any repairs are considered substantial improvement regardless of the actual repair work performed. The term does not, however, include either:

- (1) Any project for improvement of a building required to correct existing health, sanitary, or safety code violations identified by the building official and that are the minimum necessary to assure safe living conditions.
- (2) Any alteration of a historic structure provided the alteration will not preclude the structure's continued designation as a historic structure.

Variance. A grant of relief from the requirements of this article, or the flood resistant construction requirements of the Florida Building Code, which permits construction in a manner that would not otherwise be permitted by this article or the Florida Building Code.

Watercourse. A river, creek, stream, channel or other topographic feature in, on, through, or over which water flows at least periodically.

DIVISION 3. - FLOOD RESISTANT DEVELOPMENT SECTION

Sec. 23-301. - Buildings and structures.

23-301.1 Design and construction of buildings, structures and facilities exempt from the Florida Building Code. Pursuant to section 23-104.2.1 of this article, buildings, structures, and facilities that are exempt from the Florida Building Code, including substantial improvement or repair of substantial damage of such buildings, structures and facilities, shall be designed and constructed in accordance with the flood load and flood resistant construction requirements of ASCE 24. Structures exempt from the Florida Building Code that are not walled and roofed buildings shall comply with the requirements of ~~division 3, subdivision VII~~ 23-307 of this article.

23-301.2 Specific methods of construction and requirements. ~~Pursuant to Chapter 8 Article III of the Miami-Dade County Code, the~~ The following specific methods of construction and requirements apply:

(1) *Additional elevation of buildings.*

- a. For buildings located in the special flood hazard area, the minimum elevation requirements in the Florida Building Code shall be to or above the base flood elevation plus one foot, or the back of the sidewalk

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

elevation plus one foot, or if there is no sidewalk, the elevation of the crown of the road or street abutting such building site plus one foot, whichever is higher.

- b. For residential buildings not located in the special flood hazard area, the minimum lowest floor elevation requirements shall be of a minimum of eight inches above the back of sidewalk elevation, or if there is no sidewalk, a minimum of eight inches above the elevation of the crown of road or street abutting such building site whichever is higher.
- c. For non-residential buildings not located the special flood hazard area, the minimum lowest floor elevation shall be a minimum of four inches above the back of sidewalk, or if there is no sidewalk, a minimum of four inches above the elevation of the crown of road or street abutting such building site, whichever is higher.

(2) *Limitations on enclosures under elevated buildings.* For buildings applications for enclosed areas under elevated buildings shall be accompanied by a nonconversion agreement. Enclosures shall:

- a. Have the minimum necessary access to allow for parking of vehicles (garage door), limited storage of maintenance equipment used in connection with the premises (standard exterior door), or entry to the elevated building (stairway or elevator).
- b. Not have the interior portion partitioned or finished into separate rooms.

(3) *Cumulative substantial improvement.* A local government that is participating in the National Flood Insurance Program may not adopt or enforce an ordinance for substantial improvements or repairs to a structure which includes a cumulative substantial improvement period as of June 26th, 2025 as per Senate Bill (SB) 180. In the Florida Building Code, Building, and Florida Building Code, Existing Building, definitions for the term "substantial improvement" shall be as follows:

Substantial improvement. Any combination of repair, reconstruction, rehabilitation, addition, or other improvement of a building or structure taking place during a five-year period, the cumulative cost of which equals or exceeds 50 percent of the market value of the building or structure before the improvement or repair is started. For each building or structure, the five-year period begins on the date of the first improvement or repair of that building or structure subsequent to March 12, 2008. If the structure has incurred "substantial damage," any repairs are considered substantial improvement regardless of the actual repair work performed. The term does not, however, include either:

- a. Any project for improvement of a building required to correct existing health, sanitary, or safety code violations identified by the building official and that are the minimum necessary to assure safe living conditions.
- b. Any alteration of a historic structure provided the alteration will not preclude the structure's continued designation as a historic structure.

- (4) *Flood damage and substantial damage.* As defined in Florida Building Code, Building FBC Section 202. In the Florida Building Code, Building, and Florida Building Code, Existing Building, definitions for the term "substantial damage" shall be as follows:

Substantial damage.

Substantial improvement.

Substantial structural damage.

~~Damage of any origin sustained by a building or structure whereby the cost of restoring the building or structure to its before-damaged condition would equal or exceed 50 percent of the market value of the building or structure before the damage occurred. The term also includes flood-related damage sustained by a structure on two separate occasions during a ten-year period for which the cost of repairs at the time of each such flood event, on average, equals or exceeds 25 percent of structure before the damage occurred.~~

23-301.3. Accessory structures. Accessory structures are permitted below the base flood elevation provided the accessory structures are used only for parking or storage and:

- (1) Are one-story and not larger than 600 sq. ft.
- (2) Have flood openings in accordance with Section R322.2 of the Florida Building Code, Residential.
- (3) Are anchored to resist flotation, collapse or lateral movement resulting from flood loads.
- (4) Have flood damage-resistant materials used below the base flood elevation plus one (1) foot.
- (5) Have mechanical, plumbing and electrical systems, including plumbing fixtures, elevated to or above the base flood elevation plus one (1) foot.

Sec. 23-302. - Subdivisions.

23-302.1 Minimum requirements. Subdivision proposal shall be reviewed to determine that:

- (1) Such proposals are consistent with the need to minimize flood damage and will be reasonably safe from flooding;
- (2) All public utilities and facilities such as sewer, gas, electric, communications, and water systems are located and constructed to minimize or eliminate flood damage; and
- (3) Adequate drainage is provided to reduce exposure to flood hazards; in zones AH and AO, adequate drainage paths shall be provided to guide floodwaters around and away from proposed structures.

23-302.2 Subdivision plats. Where any portion of proposed subdivisions lies within a flood hazard area, the following shall be required:

- (1) Delineation of flood hazard areas, floodway boundaries and flood zones, and design flood elevations, as appropriate, shall be shown on preliminary plats;
- (2) Where the subdivision has more than 50 lots or is larger than five acres and base flood elevations are not included on the FIRM, the base flood elevations determined in accordance with section 23-105.2(1) of this article; and
- (3) Compliance with the site improvement and utilities requirements of section 23- 303 of this article.

Sec. 23-303. - Site improvements, utilities and limitations.

23-303.1 Minimum requirements. All proposed new development shall be reviewed to determine that:

- (1) Such proposals are consistent with the need to minimize flood damage and will be reasonably safe from flooding;
- (2) All public utilities and facilities such as sewer, gas, electric, communications, and water systems are located and constructed to minimize or eliminate flood damage; and
- (3) Adequate drainage is provided to reduce exposure to flood hazards; in zones AH and AO, adequate drainage paths shall be provided to guide floodwaters around and away from proposed structures.
- (4) Encroachments, including fill and structures, are not located within a distance of 20 feet from the top of the bank of any watercourse unless the application includes certification by a registered professional engineer is provided that demonstrates such encroachment does not result in any increase in flood levels during the occurrence of the base flood discharge.

23-303.2 Sanitary sewage facilities. All new and replacement sanitary sewage facilities, private sewage treatment plants (including all pumping stations and collector systems), and on-site waste disposal systems shall be designed in accordance with the standards for onsite sewage treatment and disposal systems in Chapter 64E-6, F.A.C. and ASCE 24 Chapter 7 to minimize or eliminate infiltration of floodwaters into the facilities and discharge from the facilities into flood waters, and impairment of the facilities and systems.

23-303.3 Water supply facilities. All new and replacement water supply facilities shall be designed in accordance with the water well construction standards in Chapter 62- 532.500, F.A.C. and ASCE 24 Chapter 7 to minimize or eliminate infiltration of floodwaters into the systems.

23-303.4 Limitations on sites in regulatory floodways. No development, including but not limited to site improvements, and land disturbing activity involving fill or re-grading, shall be authorized in the regulatory floodway unless the floodway encroachment analysis required in section 23-105.3(1) of this article demonstrates

that the proposed development or land disturbing activity will not result in any increase in the base flood elevation.

23-303.5 Limitations on placement of fill. Subject to the limitations of this article, fill shall be designed to be stable under conditions of flooding including rapid rise and rapid drawdown of floodwaters, prolonged inundation, and protection against flood-related erosion and scour. In addition to these requirements, if intended to support buildings and structures (zone A only), fill shall comply with the requirements of the Florida Building Code.

Sec. 23-304. - Manufactured homes.

23-304.1 General. Manufactured homes are not permitted in the City of Doral.

Sec. 23-305. - Recreational vehicles and park trailers.

Sec. 23-305.1 Temporary placement. Recreational vehicles and park trailers placed temporarily in flood hazard areas shall:

- (1) Be on the site for fewer than 180 consecutive days; or
- (2) Be fully licensed and ready for highway use, which means the recreational vehicle or park model is on wheels or jacking system, is attached to the site only by quick-disconnect type utilities and security devices, and has no permanent attachments such as additions, rooms, stairs, decks and porches.

23-305.2 Permanent placement. Permanent placement of recreational vehicles and park trailers is not permitted.

Sec. 23-306. - Tanks.

23-306.1 Underground tanks. Underground tanks shall be anchored to prevent flotation, collapse or lateral movement resulting from hydrodynamic and hydrostatic loads during conditions of the design flood, including the effects of buoyancy assuming the tank is empty.

23-306.2 Above-ground tanks, not elevated. Above-ground tanks that do not meet the elevation requirements of section 23-306.3 of this article shall be permitted provided the tanks are anchored or otherwise designed and constructed to prevent flotation, collapse or lateral movement resulting from hydrodynamic and hydrostatic loads during conditions of the design flood, including the effects of buoyancy assuming the tank is empty and the effects of flood-borne debris.

23-306.3 Above-ground tanks, elevated. Above-ground tanks shall be attached to and elevated to or above the design flood elevation on a supporting structure that is designed to prevent flotation, collapse or lateral movement during conditions of the design flood. Tank-supporting structures shall meet the foundation requirements of the applicable flood hazard area.

23-306.4 Tank inlets and vents. Tank inlets, fill openings, outlets and vents shall be:

- (1) At or above the design flood elevation or fitted with covers designed to prevent

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

the inflow of floodwater or outflow of the contents of the tanks during conditions of the design flood; and

- (2) Anchored to prevent lateral movement resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy, during conditions of the design flood.

Sec. 23-307. - Other development.

23-307.1 General requirements for other development. All development, including man- made changes to improved or unimproved real estate for which specific provisions are not specified in this article or the Florida Building Code, shall:

- (1) Be located and constructed to minimize flood damage;
- (2) Meet the limitations of section 23-303.4 of this article if located in a regulated floodway;
- (3) Be anchored to prevent flotation, collapse or lateral movement resulting from hydrostatic loads, including the effects of buoyancy, during conditions of the design flood;
- (4) Be constructed of flood damage-resistant materials; and
- (5) Have mechanical, plumbing, and electrical systems above the design flood elevation, except that minimum electric service required to address life safety and electric code requirements is permitted below the design flood elevation provided it conforms to the provisions of the electrical part of building code for wet locations.

23-307.2 Fences in regulated floodways. Fences in regulated floodways that have the potential to block the passage of floodwaters, such as stockade fences and wire mesh fences, shall meet the limitations of section 23-303.4 of this article.

23-307.3 Retaining walls, sidewalks and driveways in regulated floodways. Retaining walls and sidewalks and driveways that involve the placement of fill in regulated floodways shall meet the limitations of section 23-303.4 of this article.

23-307.4 Roads and watercourse crossings in regulated floodways. Roads and watercourse crossings, including roads, bridges, culverts, low-water crossings and similar means for vehicles or pedestrians to travel from one side of a watercourse to the other side, that encroach into regulated floodways shall meet the limitations of section 23-303.4 of this article. Alteration of a watercourse that is part of a road or watercourse crossing shall meet the requirements of section 23-105.3(3) of this article.

Section 3. Codification. It is the intention of the City Council and it is hereby ordained that the provisions of this Ordinance shall become and made part of the City of Doral Code; that the sections of this Ordinance may be renumbered or relettered to accomplish such intentions; and that the word "Ordinance" shall be changed to

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.

“Section” or other appropriate word.

Section 4. Severability. That if any section, subsection, sentence, clause, phrase, word or amount of this Ordinance shall be declared unconstitutional or invalid by competent authority, then the remainder of the Ordinance shall not be affected thereby and shall remain in full force and effect.

Section 5. Conflicts. All ordinances or parts of ordinances inconsistent or in conflict with the provisions of this Ordinance are hereby repealed.

Section 6. Effective Date. This Ordinance shall be effective immediately upon passage by the City Council on second reading.

The foregoing Ordinance was offered by _____, who moved its adoption. The motion was seconded by _____ upon being put to a vote, the vote was as follows:

Mayor Christi Fraga	_____
Vice Mayor Maureen Porras	_____
Councilwoman Digna Cabral	_____
Councilman Rafael Pineyro	_____
Councilwoman Nicole Reinoso	_____

PASSED AND ADOPTED on FIRST READING this 8 day of October, 2025.

PASSED AND ADOPTED on SECOND READING this 12 day of November, 2025.

CHRISTI FRAGA, MAYOR

ATTEST:

CONNIE DIAZ, MMC
CITY CLERK

APPROVED AS TO FORM AND LEGAL SUFFICIENCY
FOR THE USE AND RELIANCE OF THE CITY OF DORAL ONLY:

LORENZO COBIELLA
GASTESI, LOPEZ, MESTRE & COBIELLA, PLLC
CITY ATTORNEY

CODING: Additions to existing text are shown by underline, changes to existing text on second reading are shown by double underline, and deletions are shown as ~~strike through~~.